





仅供参考


REV.	REVISION RECORD	DATE
A0	新图面发行	2017.06.16

Specification:
 Current Rating : 7AMP
 Temperature Range : -40°Cto+105°C
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstanding Voltage : AC 1000V
 Material:
 Insulator : Polyester (UL94V-0)
 Standard:PA6T/LCP
 Contact: Brass
 Plating : Au or Sn Over 50u" Ni



Pin数	尺寸A	尺寸B
1×1	-	3.96
1×2	3.96	7.92
1×3	7.92	11.88
1×4	11.88	15.84
1×5	15.84	19.80
1×6	19.80	23.76
1×7	23.76	27.72
1×8	27.72	31.68
1×9	31.68	35.64
1×10	35.64	39.60
1×11	39.60	43.56
1×12	43.56	47.52
1×13	47.52	51.48
1×14	51.48	55.44
1×15	55.44	59.40
1×16	59.40	63.36
1×17	63.36	67.32
1×18	67.32	71.28
1×19	71.28	75.24
1×20	75.24	79.20

PCB LAYOUT



	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	深圳市思拓展电子有限公司 SHENZHEN SINTOP ELECTRONICS CO.,LTD 公司网址: www.szsituo.cn 公司电话: 0755-23765350 邮 箱: 2850175982@qq.com 公司传真: 0755-23765341	PART. NO: ST-PH-396-0116
	LINEAR	ANGLES					APPROVED
UNIT: MM	0.0±0.30	X° REF±6°	DESIGNER			TITLE: Pitch3.96mm Pin Header, Single Plastic, Single Row, Right Angle Type	REV: A0
SIZE: A4	0.000±0.10	X° X'±2°	DRAWN	肖坤权	2017.06.16		SHEET: 1/1